

Lubricating oil for high temperature

MORESCO-HILUBE L-150**◆ Description**

MORESCO-HILUBE L-150 is the synthetic lubricant based on alkyl-diphenyl-ether, which is prepared by MORESCO's unique synthesizing and refining technology, and suitable for the lubrication systems at high temperature.

MORESCO HILUBE L-150 is used for the lubrication of chain and sliding in Heat setter, Steamer, Tenter and Dryer which face at high temperature atmosphere, and its superior quality has been well recognized by customers.

◆ Characteristics*☆ Excellent thermal stability*

Expect the long term service life by maintaining its liquid phase at high temperature.

☆ Low evaporation Loss

Minimize the fluid supply.

☆ High flash point

Provide to use at high temperature.

◆ General property

		L-150
Density	g/cm ³ (15°C)	0.896
Color	ASTM color	L0.5
Flash point	°C	284
Viscosity	mm ² /s (40°C)	150
	mm ² /s (100°C)	17.3
Viscosity index		124

◆ How to use

Use as the chain oil for Heat setter, Steamer, Tenter and Dryer.

◆ Storage

Please refer to Material Safety Data Sheet (M.S.D.S.)

◆ Package

1 liters / tin 4 liters / tin 20 liters / can 200 liters / drum

株式会社 MORESCO

URL : <http://www.moresco.co.jp/>
 カスタマーセンター (お客様お問合せ専用窓口)
 TEL : 06-6262-3385
 E-Mail : customercenter@moresco.co.jp

MORESCO Corporation

Head Office: 5-5-3, Minatojiminami-machi, chuo-ku, Kobe-city, Hyogo, Japan
 R&D Center Phone: 078-303-9010 Fax: 078-303-9020
 Tokyo Branch: Ryoshinyaesu-Bldg., 2-8-5, Yaesu, Chuo-ku, Tokyo, Japan
 (International Business Division) Phone: 03-3273-7526 Fax: 03-3281-7756