

Lubricating oil for high temperature

MORESCO-HILUBE L-560
 Nonfood Compounds
 Program Listed H2
 Registration # 148721
◆ *Description*

MORESCO-HILUBE L-560 is the synthetic lubricant based on alkyl-diphenyl-ether, which is prepared by MORESCO's unique synthesizing and refining technology, and suitable for the lubrication systems at high temperature.

MORESCO HILUBE L-560 is used for the lubrication of chain and sliding in Heat setter, Steamer, Tenter and Dryer which face at high temperature atmosphere, and its superior quality has been well recognized by customers.

◆ *Characteristics*☆ *Excellent thermal stability*

Expect the long term service life by maintaining its liquid phase at high temperature.

☆ *Low evaporation Loss*

Minimize the fluid supply.

☆ *High flash point*

Provide to use at high temperature.

◆ *General property*

| | | L-560 |
|-----------------|-----------------------------|-------|
| Density | g/cm ³ (15 °C) | 0.896 |
| Color | ASTM color | L0.5 |
| Flash point | °C | 272 |
| Viscosity | mm ² /s (40°C) | 560 |
| | mm ² /s (100 °C) | 42 |
| Viscosity index | | 121 |

◆ *How to use*

Use as the chain oil for Heat setter, Steamer, Tenter and Dryer.

◆ *Storage*

Please refer to Safety Data Sheet (S.D.S.)

◆ *Package*

1 liter / tin 4 liters / tin 20 liters / can 200 liters / drum

株式会社 **MORESCO**

URL : <http://www.moresco.co.jp/>
 カスタマーセンター (お客様お問合せ専用窓口)
 TEL : 06-6262-3385
 E-Mail : customercenter@moresco.co.jp

MORESCO Corporation

Head Office: 5-5-3, Minatojimaminami-machi, chuo-ku, Kobe-city, Hyogo, Japan
 R&D Center Phone: 078-303-9010 Fax: 078-303-9020
 Osaka Branch: 2-15, BINGOMACHI, 3-CHOME, CHUO-KU, OSAKA, JAPAN 541-0051
 (Synthetic Lubricants Division) Phone: 06-6262-3310 Fax: 06-6262-3327