

Lubricating oil for high temperature

MORESCO-HILUBE LB-100

MORESCO-HILUBE LB-100 is the synthetic lubricant based on alkyl-diphenyl-ether, which is prepared by MORESCO's unique synthesizing and refining technology, and suitable for the lubrication systems at high temperature.

MORESCO HILUBE LB-100 is used for the based oil of grease and other lubricant which face at high temperature atmosphere, and its superior quality has been well recognized by customers.

Characteristic

1. Excellent thermal stability

Expect the long term service life by maintaining its liquid phase at high temperature.

2. Low evaporation Loss

Minimize the fluid supply.

3. High flash point

Provide to use at high temperature.

General property

		General property
Aspect		pale yellow
Density	15°C g/cm ³	0.895
Color	ASTM	L0.5
Flash point	°C	286
Viscosity	40°C mm ² /s	102.0
	100°C mm ² /s	12.6
Viscosity index		118

How to use

Use as the based oil for lubricant and grease of high temperature.

Package

1 liter/tin 4 liters/tin 20 liters/can 200 liters/drum

Storage

Please refer to Material Safety Data Sheet (M. S. D. S.)

株式会社 MORESCO

URL : <http://www.moresco.co.jp/>

カスタマーセンター (お客様お問合せ専用窓口)

TEL : 06-6262-3385

E-Mail : customercenter@moresco.co.jp

MORESCO Corporation

Head Office:5-5-3, Minatojimaminami-machi, chuo-ku, Kobe-city, Hyogo, Japan

R&D Center

Phone:078-303-9010 Fax:078-303-9020

Osaka Branch:2-15, BINGOMACHI, 3-CHOME, CHUO-KU, OSAKA, JAPAN 541-0051

(Synthetic Lubricants Division) Phone:06-6262-3310 Fax:06-6262-3327