

Grinding Coolant

MORESCO TOOLMATE GR-2

Characteristics

1. Excellent Grinding Property

Wonderful finish of the product and the extension of service life of the grindstone.

2. Excellent anti-foaming.

Prevents foaming troubles even with high pressure pumps.

3. Excellent rust prevention.

Prevents rust problems on machine and work-pieces.

4. Non Chroline, PRTR free

Property

Undiluted Fluid

		General Properties
JIS Standard Group		A3-1
Appearance		Clear Liquid
Density	15°C g/cm ³	1.05
Viscosity	40°C mm ² /s	2
Flash Point	°C	None



The appearance may change darker yellow, but no problem to use.

Diluted Fluid (x20)

Appearance	Clear Liquid
pH	10.4



Application

Suitable for grinding process of steel and cast iron
 Refracter.Brix F=3.7 (3wt%=0.8Brix%, 5wt%= 1.4Brix%)

Packages

18L/ Can 200L/ Drum

Hazardous

Non Hazardous (Japanese Fire Defense Law)

株式会社 **MORESCO**

URL : <http://www.moresco.co.jp>

Customer Center

TEL : +81-6-6262-3385

E-mail : customercenter@moresco.co.jp

MORESCO Corporation

Head Office : 5-5-3, Minatojimaminami-machi, Chuo-ku, Kobe, Japan

TEL:+81-78-303-9010 FAX:+81-78-303-9020

Osaka Branch : 3-2-15, Bingo-machi, Chuo-ku, Osaka, Japan

TEL:+81-6-6262-3310 FAX:+81-6-6262-3327