

**NEW**

Grinding Coolant for Glass Edging

MORESCO COMPANY  
**MORESCO**  
No. 2006-08609-04

# MORESCO TOOLMATE GR-5

Character  
istics

### 1. Excellent Grinding Property

Good compatibility with diamond grinding stone, provide better finish and longer dress interval.

### 2. Reduce Water-Mark trouble

Keep work-piece wet, therefore, reduce Water-Mark trouble immediately.

### 3. Quick sludge deposit, And prevent sludge solidification.

Reduce downtime, provide easy coolant tank maintenace.

### 4. Human friendly.

Lower pH, much less skin irritation, and less chemical smell.

Attn.) This product is only for glass edging grinding process.  
For other grinding purpose, please choice other product.

New! QR Link to youtube



Comparison of Sludge



Property

Undiluted Fluid

		General Properties
JIS Standard Group		A3-1
Appearance		Clear Liquid
Density	15°C g/cm <sup>3</sup>	1.08
Viscosity	40°C mm <sup>2</sup> /s	2
Flash Point	°C	None

Diluted Fluid (x20)

Appearance	Clear Liquid
pH	9.0



Application

Grinding coolant for glass edging propose. (Automotive/Architecture)  
Refracter F=2.9 (3wt%=1.0Brix%, 5wt%= 1.7Brix%)

Packages

18L/ Can                      200L/ Drum

Hazardous

Please refer the SDS.

株式会社 **MORESCO**

URL : <http://www.moresco.co.jp>  
Customer Center  
TEL : +81-6-6262-3385  
E-mail : [customercenter@moresco.co.jp](mailto:customercenter@moresco.co.jp)

**MORESCO Corporation**

Head Office : 5-5-3, Minatojimaminami-machi, Chuo-ku, Kobe, Japan  
TEL:+81-78-303-9010 FAX:+81-78-303-9020  
Osaka Branch : 3-2-15, Bingo-machi, Chuo-ku, Osaka, Japan  
TEL:+81-6-6262-3310 FAX:+81-6-6262-3327